Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

Claim 1 (withdrawn). A method of making a dual performance nonwoven laminate comprising dual performance nonwoven laminate comprising an abrasive side and an opposing absorbent side comprising the steps of:

a. providing an absorbent precursor web;

b. providing a polymeric resin;

c. extruding said polymeric resin into filaments in the range of 5-50 microns;

d. collecting said filaments onto said absorbent precursor web to form a laminate;

e. advancing said laminate onto said three-dimensional image transfer device wherein said filaments are facing the hydraulic jets and said absorbent web is facing the three-dimensional image transfer device; and

hydroentangling said laminate so as to provide for a dual performance nonwoven laminate comprising an abrasive side and an opposing absorbent side.

Claim 2 (withdrawn). A method of making a dual performance nonwoven laminate comprising an abrasive side and an opposing absorbent side comprising the steps of:

a. providing an absorbent precursor web;

b. providing a three-dimensional image transfer device;

c. providing a meltblown precursor web comprising filaments in the range of 5-50 microns;

d. juxtaposing said absorbent precursor web with said precursor meltblown web;

e. advancing said precursor webs onto said three-dimensional transfer device wherein said meltblown web is facing the hydraulic jets and said absorbent web is facing said three-dimensional transfer device; and

hydroentangling said precursor webs so as to provide for a dual performance nonwoven laminate comprising an abrasive side and an opposing absorbent side.

Claim 3 (withdrawn). A method of making a dual performance nonwoven laminate comprising an abrasive side and an opposing absorbent side comprising the steps of:

a. providing an absorbent precursor web;

b. providing a three-dimensional image transfer device;

c. providing a meltblown precursor web comprising filaments in the range of 5-50 microns;

d. juxtaposing said absorbent precursor web with said precursor meltblown web;

e. advancing said precursor webs onto said three-dimensional transfer device wherein said absorbent web is facing the hydraulic jets and said meltblown web is facing said three-dimensional transfer device; and

hydroentangling said precursor webs so as to provide for a dual performance nonwoven laminate comprising an abrasive side and an opposing absorbent side.

Claim 4 (currently amended). A dual performance nonwoven laminate ~~formed in accordance with the method of claim 1~~ comprising an abrasive side and an opposing absorbent side, formed by providing an absorbent precursor web, providing a polymeric resin, extruding the polymeric resin into filaments in the range of 5 to 50 microns, collecting the filaments onto

the absorbent precursor web to form a laminate, advancing the laminate onto a three-dimensional image transfer device, wherein the filaments are facing hydraulic jets thereof, and the absorbent precursor web is facing the three-dimensional image transfer device, and hydroentangling the laminate so as to provide a dual performance nonwoven laminate comprising an abrasive side and an opposing absorbent side.

Claim 5 (currently amended). A dual performance wipe ~~wherein said wipe is formed in accordance with the method of claim 2~~ having an abrasive side and an opposing absorbent side, formed by providing an absorbent precursor web, providing a three-dimensional image transfer device, providing a meltblown precursor web comprising filaments in the range of 5 to 50 microns, juxtaposing the absorbent precursor web with the precursor meltblown web, advancing the precursor webs onto the three-dimensional image transfer device wherein the meltblown web is facing hydraulic jets of the image transfer device and the absorbent web is facing a three-dimensional surface of the image transfer device, and hydroentangling the precursor webs so as to provide a dual performance nonwoven laminate comprising an absorbent side and an opposing side.

Claim 6 (currently amended). A dual performance wipe ~~wherein said wipe is formed~~ in accordance with the method of claim ~~3~~ 5, and which further comprises a cleaning agent.